


**FEATURES**

- ▶ Industrial Standard 2"x1" Package
- ▶ Wide 2:1 Input Voltage Range
- ▶ Fully Regulated Output Voltage
- ▶ Ultra-high I/O Isolation 8000VDC with Reinforced Insulation, rated for 1000Vrms Working Voltage
- ▶ Wide Operating Temperature Range
- ▶ No Min. Load Requirement
- ▶ Under-voltage, Overload/Voltage and Short Circuit Protection
- ▶ EMI Emission EN55032 Class A Approved
- ▶ UL/cUL/IEC/EN 62368-1 & UL/cUL 60950-1 Safety Approval & CE Marking


**PRODUCT OVERVIEW**

The MKE15-HI Series is a family of 15W isolated, fully regulated DC-DC converters in an industry-standard 2" x 1" package, designed for applications that require extra-high isolation and compliance-ready performance. It supports a wide 2:1 input voltage range and provides stable regulated output for reliable system operation.

Featuring ultra-high 8000VDC reinforced insulation with a rated 1000Vrms working voltage, the series delivers strong safety margin and isolation robustness. It also offers a wide operating temperature range, no minimum load requirement, and built-in protections including under-voltage, overload/over-voltage, and short-circuit protection. Compliance support includes EN 55032 Class A EMI emission performance, plus UL/cUL/IEC/EN 62368-1 & UL/cUL 60950-1 safety approvals and CE marking.

**Model Selection Guide**

Model Number	Input Voltage (Range) VDC	Output Voltage VDC	Output Current Max. mA	Input Current		Reflected Ripple Current mA(typ.)	Over Voltage Protection VDC	Max. capacitive Load µF	Efficiency (typ.)
				@Max. Load mA(typ.)	@No Load mA (typ.)				@Max. Load %
MKE15-12S05HI	12 (9 ~ 18)	5	3000	1471	20	100	6.2	5100	85
MKE15-12S051HI		5.1	3000	1500			6.2		85
MKE15-12S12HI		12	1250	1420			15	870	88
MKE15-12S15HI		15	1000	1420			18	560	88
MKE15-12S24HI		24	625	1420			27	220	88
MKE15-12D12HI		±12	±625	1420			±15	440#	88
MKE15-12D15HI		±15	±500	1404			±18	280#	89
MKE15-24S05HI	24 (18 ~ 36)	5	3000	718	15	50	6.2	5100	87
MKE15-24S051HI		5.1	3000	733			6.2		87
MKE15-24S12HI		12	1250	710			15	870	88
MKE15-24S15HI		15	1000	702			18	560	89
MKE15-24S24HI		24	625	694			27	220	90
MKE15-24D12HI		±12	±625	694			±15	440#	90
MKE15-24D15HI		±15	±500	702			±18	280#	89
MKE15-48S05HI	48 (36 ~ 75)	5	3000	359	10	30	6.2	5100	87
MKE15-48S051HI		5.1	3000	366			6.2		87
MKE15-48S12HI		12	1250	359			15	870	87
MKE15-48S15HI		15	1000	347			18	560	90
MKE15-48S24HI		24	625	351			27	220	89
MKE15-48D12HI		±12	±625	351			±15	440#	89
MKE15-48D15HI		±15	±500	355			±18	280#	88

# For each output

Input Specifications						
Parameter	Conditions / Model	Min.	Typ.	Max.	Unit	
Input Surge Voltage (100 ms max.)	12V Input Models	-0.7	---	25	VDC	
	24V Input Models	-0.7	---	50		
	48V Input Models	-0.7	---	100		
Start-Up Threshold Voltage	12V Input Models	---	---	9		
	24V Input Models	---	---	18		
	48V Input Models	---	---	36		
Under Voltage Shutdown	12V Input Models	---	7.5	---		
	24V Input Models	---	15	---		
	48V Input Models	---	33	---		
Start Up Time (Power On)	Nominal Vin and Constant Resistive Load	---	---	30	ms	
Input Filter	All Models	Internal Pi Type				

Output Specifications							
Parameter	Conditions / Model	Min.	Typ.	Max.	Unit		
Output Voltage Setting Accuracy		---	---	±1.0	%Vnom.		
Output Voltage Balance	Dual Output, Balanced Loads	---	---	±2.0	%		
Line Regulation	Vin=Min. to Max. @Full Load	---	---	±0.5	%		
Load Regulation	Io=0% to 100%	Single Output	---	---	±0.5	%	
		Dual Output	---	---	±1.0	%	
Minimum Load	No minimum Load Requirement						
Ripple & Noise	0-20 MHz Bandwidth	5V & 5.1Vo	Measured with a MLCC : 4.7µF	---	50	---	mV <sub>P-P</sub>
		12V,15V, ±12V, ±15Vo		---	100	---	mV <sub>P-P</sub>
		24Vo		---	150	---	mV <sub>P-P</sub>
Transient Recovery Time	25% Load Step Change <sub>(2)</sub>	---	---	300	µs		
Transient Response Deviation		---	±3	±5	%		
Temperature Coefficient		---	---	±0.02	%/°C		
Over Load Protection	Hiccup	---	150	---	%		
Short Circuit Protection	Continuous, Automatic Recovery (Hiccup Mode 0.7Hz typ.)						

Isolation, Safety Standards						
Parameter	Conditions	Min.	Typ.	Max.	Unit	
I/O Isolation Voltage	60 Seconds Reinforced insulation, rated for 1000Vrms working voltage	4200	---	---	VAC	
	Tested for 1 second	8000	---	---	VDC	
I/O Isolation Resistance	500 VDC	10	---	---	GΩ	
I/O Isolation Capacitance	100kHz, 1V	---	---	80	pF	
Safety Approvals	UL/cUL 60950-1 recognition (UL certificate)					
	UL/cUL 62368-1 recognition (UL certificate), IEC/EN 62368-1(CB-report)					

**General Specifications**






Parameter	Conditions	Min.	Typ.	Max.	Unit
Switching Frequency		---	285	---	kHz
MTBF(calculated)	MIL-HDBK-217F@25°C, Ground Benign	1,428,181	---	---	Hours

**EMC Specifications**


Parameter	Standards & Level			Performance
EMI	Conduction	EN 55032	Without external components	Class A
	Radiation			
EMS <sub>(5)</sub>	EN 55035			A
	ESD	Direct discharge	Indirect discharge HCP & VCP	
		EN 61000-4-2 Air ± 15kV	Contact ± 8kV	
	Radiated immunity	EN 61000-4-3 10V/m		A
	Fast transient	EN 61000-4-4 ±2kV		A
	Surge	EN 61000-4-5 ±1kV		A
	Conducted immunity	EN 61000-4-6 10Vrms		A
PFMF	EN 61000-4-8 100A/m		A	

**Environmental Specifications**

Parameter	Conditions / Model	Min.	Max.	Unit
Operating Ambient Temperature Range Nominal Vin, Load 100% Inom. (for Power Derating see relative Derating Curves)	MKE15-24S24HI, MKE15-24D12HI, MKE15-48S15HI	-40	+73	°C
	MKE15-12D15HI, MKE15-24S15HI, MKE15-24D15HI MKE15-48S24HI, MKE15-48D12HI		+70	
	MKE15-12S12HI, MKE15-12S15HI, MKE15-12S24HI MKE15-12D12HI, MKE15-24S12HI, MKE15-48D15HI		+68	
	MKE15-24S05HI, MKE15-24S051HI, MKE15-48S05HI MKE15-48S051HI, MKE15-48S12HI		+65	
	MKE15-12S05HI, MKE15-12S051HI		+59	
Thermal Impedance		13	---	°C/W
Case Temperature		---	+95	°C
Storage Temperature Range		-50	+125	°C
Humidity (non condensing)		---	95	% rel. H
Altitude		---	4000	m
Lead Temperature (1.5mm from case for 10Sec.)		---	260	°C

**Power Derating Curve**

**MKE15-24S24HI, MKE15-24D12HI, MKE15-48S15HI**

**MKE15-12D15HI, MKE15-24S15HI, MKE15-24D15HI  
MKE15-48S24HI, MKE15-48D12HI**

**MKE15-12S12HI, MKE15-12S15HI, MKE15-12S24HI  
MKE15-12D12HI, MKE15-24S12HI, MKE15-48D15HI**

**MKE15-24S05HI, MKE15-24S051HI, MKE15-48S05HI  
MKE15-48S051HI, MKE15-48S12HI**

**MKE15-12S05HI, MKE15-12S051HI**
**Notes**

- 1 Specifications typical at  $T_a = +25^\circ\text{C}$ , resistive load, nominal input voltage and rated output current unless otherwise noted.
- 2 Transient recovery time is measured to within 1% error band for a step change in output load of 75% to 100%.
- 3 We recommend to protect the converter by a slow blow fuse in the input supply line.
- 4 Other input and output voltage may be available, please contact MINMAX.
- 5 The external components might be required to meet EMS standard for some of test items. Please contact MINMAX for the solution in detail.
- 6 Specifications are subject to change without notice.
- 7 The repeated high voltage isolation testing of the converter can degrade isolation capability, to a lesser or greater degree depending on materials, construction, environment and reflow solder process. Any material is susceptible to eventual chemical degradation when subject to very high applied voltages thus implying that the number of tests should be strictly limited. We therefore strongly advise against repeated high voltage isolation testing, but if it is absolutely required, that the voltage be reduced by 20% from specified test voltage. Furthermore, the high voltage isolation capability after reflow solder process should be evaluated as it is applied on system.

**Package Specifications**
**Mechanical Dimensions**

**Pin Connections**

Pin	Single Output	Dual Output	Diameter mm (inches)
1	+Vin	+Vin	∅ 1.0 [0.04]
2	-Vin	-Vin	∅ 1.0 [0.04]
3	+Vout	+Vout	∅ 1.0 [0.04]
4	No Pin	Common	∅ 1.0 [0.04]
5	-Vout	-Vout	∅ 1.0 [0.04]


- ▶ All dimensions in mm (inches)
- ▶ Tolerance: X.X±0.5 (X.XX±0.02)  
X.XX±0.25 (X.XXX±0.010)
- ▶ Pin diameter tolerance: X.X±0.05 (X.XX±0.002)

**Physical Characteristics**



Case Size	: 50.8x25.4x12.1mm (2.0x1.0x0.48 inches)
Case Material	: Plastic resin (flammability to UL 94V-0 rated)
Pin Material	: Copper Alloy
Weight	: 30g

**Test Setup**
**Input Reflected-Ripple Current Test Setup**

Input reflected-ripple current is measured with an inductor  $L_{in}$  (4.7 $\mu$ H) and  $C_{in}$  (220 $\mu$ F, ESR < 1.0 $\Omega$  at 100 kHz) to simulate source impedance. Capacitor  $C_{in}$  offsets possible battery impedance. Current ripple is measured at the input terminals of the module, measurement bandwidth is 0-500 kHz.


**Peak-to-Peak Output Noise Measurement Test**

Use a  $C_{out}$  4.7 $\mu$ F ceramic capacitor. Scope measurement should be made by using a BNC socket, measurement bandwidth is 0-20 MHz. Position the load between 50 mm and 75 mm from the DC-DC Converter.


**Technical Notes**
**Overload Protection**


To provide hiccup mode protection in a fault (output overload) condition, the unit is equipped with internal current limiting circuitry and can endure overload for an unlimited duration.

**Overvoltage Protection**



The output overvoltage clamp consists of control circuitry, which is independent of the primary regulation loop, that monitors the voltage on the output terminals. The control loop of the clamp has a higher voltage set point than the primary loop. This provides a redundant voltage control that reduces the risk of output overvoltage. The OVP level can be found in the output data.

**Input Source Impedance**

The power module should be connected to a low ac-impedance input source. Highly inductive source impedances can affect the stability of the power module. In applications where power is supplied over long lines and output loading is high, it may be necessary to use a capacitor on the input to insure startup. By using a good quality low Equivalent Series Resistance (ESR < 1.0 $\Omega$  at 100 kHz) capacitor of a 10 $\mu$ F for the 12V input devices and a 4.7 $\mu$ F for the 24V input devices and a 2.2 $\mu$ F for the 48V devices, capacitor mounted close to the power module helps ensure stability of the unit.


**Output Ripple Reduction**

A good quality low ESR capacitor placed as close as practicable across the load will give the best ripple and noise performance. To reduce output ripple, it is recommended to use 4.7 $\mu$ F capacitors at the output.


**Maximum Capacitive Load**

The MKE15-HI series has limitation of maximum connected capacitance on the output. The power module may operate in current limiting mode during start-up, affecting the ramp-up and the startup time. Connect capacitors at the point of load for best performance. The maximum capacitance can be found in the data sheet.

**Thermal Considerations**

Many conditions affect the thermal performance of the power module, such as orientation, airflow over the module and board spacing. To avoid exceeding the maximum temperature rating of the components inside the power module, the case temperature must be kept below 95 $^{\circ}$ C. The derating curves are determined from measurements obtained in a test setup.

